

iKONIC CLASSIC

PLATFORM LIFT

ikcla500

CORE FEATURES INCLUDE:

- ▶ Eco friendly "A" rated power consumption
- ▶ Screw & Nut Drive System
- ▶ Smooth and quiet ride quality
- ▶ Full Equality Act (**EN81-70**) compliance Available
- ▶ Space Saving
- ▶ No shaft, pit or lifting beam required


SUITABLE FOR:



LOAD CAPACITY



CAR ENTRANCES



SPEED



TRAVEL

TECHNICAL FEATURES	
LIFT TYPE	Platform
LIFT MODEL	ikcla500
STANDARDS	EN81-41 EN81-70 Machinery Directive 2006/42/EC
MAX DUTY LOAD (Kg)	500
RATED SPEED (m/s)	<0.15
STARTS PER HOUR	20
MAX LIFT TRAVEL (M)	13 (6 Stops)
PIT (mm)	50 or Ramp
HEADROOM (mm)	2250
POWER SUPPLY (TNP)	Single-phase 50/60 Hz 16 A
DRIVE SYSTEM	Screw & Nut
ENTRANCE OPTIONS	Single, Through, Adjacent Entrance
USAGE SUITABILITY	Medium
CONTROL SYSTEM	Micro computer based system
DOOR	Hinged
LANDING DOOR (mm)	900 x 2000
CAR DOOR (mm)	900 x 1100
FIRE RATING	Option for EI60G doors

**iKONIC Lifts Ltd**Telephone: 0203 376 6440 E-mail: sales@ikoniclifts.co.ukCompany Number: 11365265 www.ikoniclifts.co.uk

iKONIC CLASSIC

PLATFORM LIFT

ikcla500**FINISHES SUPPLIED AS STANDARD FOR ikclas500**

WALL	Solid 1 piece guide wall 904mm steel panels. RAL 9016*
FLOOR	Non-slip vinyl or studded rubber selected from our standard range*
HANDRAIL	Aluminium*
CEILING	The ceiling and platform are illuminated by durable and energy- saving LED lights.*
CAR STATION	Aluminium*
LANDING DOORS	Aluminium or Steel*
CONTROLLER CABINET	At the landing entrance*
LANDING FACE PLATE	Aluminium or Steel*

INDICATORS SUPPLIED AS STANDARD FOR ikclas500

CAR PUSH BUTTONS	Full set of Hold To Run in car station
EMERGENCY COMMUNICATION	Automatic dialling emergency telephone activated upon pressing alarm push*
LANDING PUSHES	Micro movement illuminating pushes, tactile legends compliant with EN81-70*
LANDING INDICATORS	Direction arrows located side of door*
FEATURES	<ul style="list-style-type: none"> • Full set of car pushes • Position indicator • Door open button • Alarm • Voice Synthesiser • Overload Indicator

**We have an extensive range of finishes and indicators any changes requested will be stated in your quotation for actual finishes.*

ADDITIONAL ITEMS INCLUDED NOT INCLUDED FOR ikclas500

INCLUDED	
DOCUMENTATION	General Arrangement Drawings Technical Manual Health & Safety Documentation Method & Risk Assessments
LIFT DELIVERY	Our offer will include delivery to site a fork lift truck with a driver will need to be provided by the contractor. The off loading area suitable for storage needs to be on the same level and adjacent to where the lift is to be installed.
INSTALLATION	Included
COMMISSIONING	Included

12 MONTH SERVICING FOR ikclas500

Service contracts available on request. Contact our service department for a
free quotation service@ikoniclifts.co.uk

12 MONTH WARRANTY FOR ikclas500

INCLUDED- Subject to the lift being maintained by ISO 9001 approved lift
service company in accordance with our recommendations

**iKONIC Lifts Ltd**Telephone: 0203 376 6440 E-mail: sales@ikoniclifts.co.ukCompany Number: 11365265 www.ikoniclifts.co.uk

iKONIC COMPARE

PLATFORM LIFTS



	iKONIC CLASSIC	iKONIC ECLIPSE	iKONIC HEAVY DUTY	iKONIC HIRO 320	iKONIC HIRO 350	iKONIC HIRO 440
STANDARDS	EN81-41 EN81-70 Machinery Directive 2006/42/EC	EN81-41 EN81-70 Machinery Directive 2006/42/EC	EN81-41 EN81-70 Machinery Directive 2006/42/EC	EN81-40	EN81-40	EN81-40 BS 6440
MAX DUTY LOAD (Kg)	500	630	1000	300	300	500
RATED SPEED (m/s)	<0.15	<0.15	<0.15	<0.1	<0.1	<0.15
STARTS PER HOUR	20	20	20	20	20	20
MAX LIFT TRAVEL (M)	13	13	13	50	50	3
PIT (mm)	50	150	130	N/A	N/A	N/A
HEADROOM (mm)	2250	2500	2300	2000	2000	2000
POWER SUPPLY (TNP)	400 V / 3 Phase 50 Hz	400V / 3 Phase 50 Hz	230V 1 Phase 5 0Hz	230 V 1 Phase 50 Hz	230 V 1 Phase 50 Hz	230 V 1 Phase 50 Hz
DRIVE SYSTEM	Screw & Nut	Screw & Nut Traction Hydraulic	Screw & Nut	Patented Traction Drive With Dual Stainless-steel Track.	Patented Traction Drive With Dual Stainless-steel Track.	Various
ENTRANCE OPTIONS	SINGLE ENTRANCE THROUGH ENTRANCE ADJACENT ENTRANCE	SINGLE ENTRANCE THROUGH ENTRANCE ADJACENT ENTRANCE	SINGLE ENTRANCE THROUGH ENTRANCE ADJACENT ENTRANCE	SINGLE ENTRANCE THROUGH ENTRANCE	SINGLE ENTRANCE THROUGH ENTRANCE	SINGLE ENTRANCE THROUGH ENTRANCE
USAGE SUITABILITY	MED	MED	MED	LOW	LOW	LOW
LIFT STRUCTURE INCLUDED	YES	YES	YES	N/A	N/A	N/A
CUSTOMISABLE	YES	YES	YES	YES	YES	YES
LOW CARBON FOOTPRINT	●	●	●	●	●	●
EQUALITY ACT	●	●	●	●	●	●